

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Patent Application for:

PC CARD RECORDER

Inventor(s): Ryuichi Iwamura

Docket Number: SNY-R4812

Prepared By:

Miller Patent Services
29 Seminole Drive
Ringwood, NJ 07456

Phone: (973) 728-2760
Fax: (973) 728-0438
Email: miller@patent-inventions.com

CERTIFICATE OF EXPRESS MAILING FOR NEW PATENT APPLICATION

"Express Mail" mailing label number EK555534198US

Date of Deposit 9/21/2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Catherine N. Miller

(Typed or printed name of person mailing paper or fee)

Catherine N. Miller

(Signature of person mailing paper or fee)

10/22/01 14:05:56

1
2
3
4
5
6
7
8
9 **PC CARD RECORDER**

10
11
12 **CROSS REFERENCE TO RELATED DOCUMENTS**

13 This application is related to U.S. Patent Application Serial No. 09/538,568,
14 Attorney Docket number SONY 50N3504, filed March 29, 2000, entitled "Secure
15 Conditional Access Port Interface" to Maruo, et al., which is hereby incorporated
16 herein by reference.

17 **FIELD OF THE INVENTION**

18 This invention relates generally to the field of digital video recording. More
19 particularly, this invention relates to a method and apparatus for recording digital
20 video signals using a Set-Top Box or other conditional access Point of Deployment
21 (POD).

22
23 **BACKGROUND OF THE INVENTION**

24 Personal Video Recorders (PVR) have recently been introduced to the
25 marketplace to permit digital recording of television broadcasts (whether over
26 cable, satellite, or other broadcast technique). Such devices record television
27 programming using a hard disc drive (HDD). A HDD generally has large memory
28 capacity and is well suited for long recording time. However, HDDs have many
29 disadvantages also. They are generally physically large, and thus an internal HDD

1 requires a relatively large space. An external HDD occupies household space on
2 the top or on the side of a Set-Top Box or TV set.

3 The recording density of a HDD is rising rapidly while the cost per bit or byte
4 is simultaneously drastically falling. However, the low end of the total cost of a
5 Hard Disc Drive may be limited by the need for a tightly sealed, durable case and
6 a HDD interface. Additionally, by its mechanical nature, a HDD is vulnerable to
7 mechanical shock and when damaged is not easy to repair. Since the HDD a
8 mechanical device, it is usually the least reliable part in a television Set-Top Box
9 or other digital television accessory. Also, replacement of a HDD may be
10 complicated since, usually, the whole of the HDD unit has to be replaced. The
11 limits of the mechanical seek time also limits the speed of certain trick play modes.

12 In addition to the above disadvantages, a HDD cannot generally be
13 considered very secure since the interface (IDE, SCSI, iLINK) is normally a
14 standard PC type interface. Thus, stored data can be easily read and pirated by
15 connecting the HDD to a PC. This is a distinct disadvantage in an environment
16 where conditional access is used to restrict viewing of copyright material to those
17 who pay the appropriate fees. Although a HDD has many advantages, it is not an
18 ideal storage medium for video recording.

19 20 **SUMMARY OF THE INVENTION**

21 The present invention relates generally to a PC card recorder suitable for
22 recording digital video. Objects, advantages and features of the invention will
23 become apparent to those skilled in the art upon consideration of the following
24 detailed description of the invention.

25 Certain embodiments of the present invention provide for methods and
26 apparatus relating to a PC card video recorder. The conditional access functionality
27 of a Point Of Deployment module (POD) is augmented by providing solid state
28 memory on a PC card for recording and playback of programming. An encrypted
29 video stream from a television Set-Top Box (STB) or other appliance is decrypted
30 in the PC card. The decrypted video stream is then filtered to remove information

1 not relevant to a program to be stored. The filtered video stream is then applied to
2 the solid state memory. During playback, the video stream is retrieved from the
3 memory and encrypted prior to transmission to the STB. Intra-pictures can be
4 played back rapidly to provide a fast forward mode by reference to a table or packet
5 header storing starting and ending address of the intra-pictures. Multiple POD card
6 interfaces can be provided in the STB to accept multiple PC card recorders.
7 Pairing security can be provided by checking a recording STB identifier against a
8 playback STB identifier.

9 Several related methods and apparatus consistent with embodiments of the
10 present invention are described in the present document. By way of exemplary
11 overview, some of these inventions can be summarized, without limitation, by the
12 following descriptions:

13 A PC card video recording device consistent with an embodiment of the
14 invention has a PCMCIA compliant connector. A decrypter receives encrypted
15 video data through the connector and decrypts the video data into a video data
16 stream. A memory and a processor are provided. A filter, receives the video data
17 stream, and sends a portion of the video data stream specified by the processor to
18 the memory for storage.

19 A PC card recording device consistent with another embodiment has a
20 PCMCIA compliant connector. A decrypter receives encrypted data through the
21 connector and decrypts the data into a data stream. A memory and a processor
22 are provided. A filter, receives the data stream and sends a portion of the data
23 stream specified by the processor to the memory for storage.

24 A PC card video recording and playback device consistent with certain
25 embodiments has a PCMCIA compliant connector and a first decrypter that
26 receives encrypted video data through the connector and decrypts the video data
27 into a video data stream. A solid state non-volatile memory and a memory
28 interface and a processor are provided. A filter, receives the video data stream, and
29 sends a portion of the video data stream associated with a packet identifier
30 specified by the processor to the memory interface for storage in the memory. A

1 reference clock sends timing information to the memory interface for storage with
2 the video data stream. A first encrypter receives data stored in the memory
3 according to a packet identifier associated with the stored data from the memory
4 interface, encrypts the data and sends the data to the connector, under control of
5 the processor.

6 A method, carried out in a PC card recorder, of storing video programming
7 on the PC card recorder, consistent with certain embodiments includes receiving
8 an encrypted video data stream; decrypting the encrypted video data stream to
9 produce a video data stream; filtering the video data stream to remove data not
10 related to a program identified by a packet identifier to produce a filtered video data
11 stream; and storing the filtered video data stream in a solid state memory.

12 Another method, carried out in a PC card recorder, of playback of video
13 programming stored on the PC card recorder, consistent with certain embodiments
14 includes identifying a packet identifier associated with a program to be played;
15 retrieving a video data stream associated with the packet identifier from a solid
16 state memory; encrypting the video data stream to produce an encrypted video data
17 stream; and sending the encrypted video data stream to a PCMCIA connector.

18 A recording module consistent with certain embodiments has a connector
19 suitable for interconnecting with a conditional access point of deployment module
20 (POD) connector in a receiver. A memory is provided and a circuit that receives
21 information through the connector stores the information on the memory.

22 Another method, consistent with certain embodiments includes receiving a
23 stream of information through a conditional access point of deployment module
24 (POD) connector in a receiver; and storing at least a portion of the stream of
25 information in a memory.

26 A PC card device consistent with certain embodiments has a PCMCIA
27 compliant connector. A decrypter receives encrypted video data through the
28 connector and decrypts the video data into a video data stream. A memory and
29 a processor are provided. A filter, receives the video data stream, and sends a
30 portion of the video data stream associated with a packet identifier specified by the

1 processor to the memory for storage. An encrypter receives data stored in the
2 memory, encrypts the data and sends the data to the connector, under control of
3 the processor.

4 A PC card device, consistent with certain embodiments has a PCMCIA
5 compliant connector. A first decrypter receives encrypted video data through the
6 connector and decrypts the video data into a video data stream. A memory and
7 processor and a second encrypter are provided. A filter receives the video data
8 stream, and sends a portion of the video data stream associated with a packet
9 identifier specified by the processor to the second encrypter for encrypting the video
10 data stream to produce an encrypted video data stream. A memory interface
11 receives the encrypted video data stream for storage in the memory, and retrieves
12 the encrypted video data stream from the memory. A second decrypter decrypts
13 the video data stream retrieved from memory. A first encrypter receives video data
14 stream from the second decrypter, encrypts the video data stream and sends the
15 encrypted video data stream to the connector, under control of the processor.

16 A video device, consistent with certain embodiments has a conditional
17 access point of deployment module (POD) interface for receiving a point of
18 deployment module. A receiver front end unit receives a signal containing video
19 information and sends a video stream to the POD interface. A circuit card coupled
20 to POD interface and receiving the video stream. A memory resides on the circuit
21 card. A memory interface resides on the circuit card for storing video content
22 forming a part of the video stream in the memory.

23 Another video device, consistent with certain embodiments has a conditional
24 access point of deployment module (POD) interface for receiving a point of
25 deployment module. A receiver front end unit receives a signal containing video
26 information and sends a video stream to the POD interface. A circuit card is
27 coupled to POD interface and receives the video stream wherein the video stream
28 is encrypted. A memory resides on the circuit card. A decrypter resides on the
29 circuit card and decrypts the encrypted video stream to produce a decrypted video
30 stream. A filter resides on the circuit card and removes information from the

1 decrypted video stream not relevant to the video content to produce a filtered video
2 stream. A memory interface resides on the circuit card for storing the filtered video
3 stream in the memory, and for retrieving the stored video stream from the memory
4 to obtain a retrieved video stream. An encrypter resides on the circuit card that
5 encrypts the retrieved video stream and sends the encrypted retrieved video stream
6 to the POD interface.

7 A method of operation of a video device, consistent with certain
8 embodiments includes sending a video stream to a conditional access point of
9 deployment module (POD) interface; receiving the video stream at a circuit card
10 coupled to the POD interface; and storing video content forming a part of the video
11 stream in a memory residing on the circuit card.

12 A video device, consistent with certain embodiments has a first conditional
13 access point of deployment module (POD) interface for receiving a first point of
14 deployment module. A second conditional access point of deployment module
15 (POD) interface receives a second point of deployment module. A receiver front
16 end receives a signal containing video information and sending a first video stream
17 to the first POD interface, and a second video stream to the second POD interface.

18 A method of recording a digital video signal, consistent with certain
19 embodiments, includes receiving a digitally encoded video signal, the signal having
20 pictures encoded as groups of pictures with the groups of pictures having intra-
21 coded pictures, and inter-coded pictures; storing the digitally encoded video signal
22 to an addressable storage device; and storing in a table a starting address and an
23 ending address for each intra-coded picture.

24 Another method consistent with certain embodiments, of retrieving a digitally
25 encoded video signal stored in an addressable electronic storage device, the signal
26 having pictures encoded as groups of pictures with the groups of pictures having
27 intra-coded pictures, and inter-coded pictures, includes for each of a plurality of
28 intra-coded pictures: looking up a starting address in a table for an intra-coded
29 picture; looking up an ending address in the table for the intra-coded picture; and
30 retrieving the intra-coded picture from the addressable storage device.

1 A method of recording a digital video signal, consistent with certain
2 embodiments includes receiving a digitally encoded video signal, the signal having
3 pictures encoded as groups of pictures with the groups of pictures having intra-
4 coded pictures, and inter-coded pictures; determining which of the pictures are
5 intra-coded pictures; storing the digitally encoded video signal to a storage device;
6 and storing in a header associated with each intra-coded picture with an identifier
7 identifying the picture to be an intra-coded picture.

8 Another method, consistent with certain embodiments, of retrieving a
9 digitally encoded video signal stored in an electronic storage device, the signal
10 having pictures encoded as groups of pictures with the groups of pictures having
11 intra-coded pictures, and inter-coded pictures, includes for each of a plurality of
12 pictures: reading a header associated with each picture; determining from an
13 identifier in the header whether the picture is an intra-coded picture; and if so,
14 retrieving the intra-coded picture.

15 A method of providing pairing security in a PC card recorder, consistent with
16 certain embodiments, includes at the PC card recorder, receiving an identifier from
17 a host device; storing the identifier in the PC card recorder; receiving a digital video
18 signal from the host device; and storing the digital video signal in a memory of the
19 PC card recorder.

20 Another method of providing pairing security in a PC card recorder,
21 consistent with certain embodiments includes receiving a request to play a stored
22 digital video signal; at the PC card recorder, retrieving a stored host device identifier
23 from a memory; at the PC card recorder, receiving an identifier from the host
24 device; at the PC card recorder, comparing the identifier with the stored identifier;
25 and playing the stored digital video signal from a memory of the PC card recorder
26 if the identifier and the stored identifier match.

27 A method of recording a television program, consistent with certain
28 embodiments includes receiving a command signal from a remote commander to
29 record a selected television program; at a host processor, determining a packet
30 identifier corresponding to the selected television program; sending the packet

1 identifier along with a record command to a POD interface; at a PC card recorder:
2 receiving a transport stream from the POD interface; receiving the packet identifier
3 and the record command from the POD interface; instructing a transport stream
4 filter to delete packets not associated with the packet identifier; and recording the
5 packets associated with the packet identifier to a memory.

6 A method of recording a television program at a PC card recorder, consistent
7 with certain embodiments includes receiving a transport stream from a POD
8 interface; receiving the packet identifier and the record command from the POD
9 interface; instructing a transport stream filter to delete packets not associated with
10 the packet identifier; and recording the packets associated with the packet identifier
11 to the PC card recorder connected to the POD interface.

12 A method of storing information from an MPEG transport stream, consistent
13 with certain embodiments includes receiving a picture from the MPEG transport
14 stream; determining a type associated with the picture; and storing a type indicator
15 along with the picture in a memory.

16 The methods described above can be carried out in a programmed
17 processor executing instructions stored in any suitable electronic storage medium.

18 The above summaries are intended to illustrate exemplary embodiments of
19 the invention, which will be best understood in conjunction with the detailed
20 description to follow, and are not intended to limit the scope of the appended
21 claims.

22 23 **BRIEF DESCRIPTION OF THE DRAWINGS**

24 The features of the invention believed to be novel are set forth with
25 particularity in the appended claims. The invention itself however, both as to
26 organization and method of operation, together with objects and advantages
27 thereof, may be best understood by reference to the following detailed description
28 of the invention, which describes certain exemplary embodiments of the invention,
29 taken in conjunction with the accompanying drawings in which:

1 **FIGURE 1** is a block diagram of an exemplary system with a POD and smart
2 card arrangement that can be used to realize certain embodiments of the present
3 invention.

4 **FIGURE 2** is a block diagram of an exemplary Set-Top Box consistent with
5 certain embodiments of the present invention.

6 **FIGURE 3** is an exemplary block diagram of a Set-Top Box with a PC card
7 recorder consistent with certain embodiments of the present invention.

8 **FIGURE 4**, which is made up of **FIGURES 4A, 4B, 4C, 4D**, and **4E** illustrate
9 the operation of a circular memory arrangement consistent with certain
10 embodiments of the present invention

11 **FIGURE 5** is another exemplary Set-Top Box accepting multiple PC card
12 recorders consistent with certain embodiments of the present invention.

13 **FIGURE 6** is an exemplary block diagram of a PC card recorder consistent
14 with an embodiment of the present invention in which additional encryption is
15 provided for enhanced security.

16 **FIGURE 7** is a flow chart depicting a process of providing pair security in a
17 recorder consistent with certain embodiments of the present invention.

18 **FIGURE 8** is a flow chart depicting a process of an intra picture recording
19 process consistent with certain embodiments of the present invention.

20 **FIGURE 9** is a flow chart depicting a process of an intra picture playback
21 process consistent with certain embodiments of the present invention.

22 **FIGURE 10** is an exemplary block diagram of a Set-Top Box with a PC card
23 recorder consistent with certain alternative embodiment of the present invention.
24

25 **DETAILED DESCRIPTION OF THE INVENTION**

26 While this invention is susceptible of embodiment in many different forms,
27 there is shown in the drawings and will herein be described in detail specific
28 embodiments, with the understanding that the present disclosure is to be
29 considered as an example of the principles of the invention and not intended to limit

1 the invention to the specific embodiments shown and described. In the description
2 below, like reference numerals are used to describe the same, similar or
3 corresponding parts in the several views of the drawings.
4

5 As used herein, the term "video" is to be given its conversational meaning
6 which may include not only pure video content, but may also include audio content
7 as well as other information. This is consistent with the term's use in, for example,
8 in "video cassette recorder", "personal video recorder", "video camera", "music
9 video", etc. and is thus not to be strictly limited to information representing pure
10 visual content. When the term is used to mean pure visual content, it is believed
11 that this will be clear from the context.

12 Digital broadcast systems include direct broadcast digital satellite systems,
13 interactive World Wide Web ("Web") access systems, and digital cable systems.
14 Digital broadcasting provides a number of advantages to subscribers, such as
15 variety and flexibility of programming; useful and comprehensive support services
16 (such as detailed electronic programming guides), and superior audio and video
17 quality.

18 The Conditional Access (CA) function of a digital broadcast system allows
19 selective access, for a fee, to premium services such as pay-per-view movies and
20 events. The producers of the movies, events, etc., sometimes require that access
21 to the premium services be controlled in order to protect their commercial interests
22 as well as to enforce copyrights and protect copyright ownership. The digital
23 broadcast system operators (also referred to as Multiple Service Operators, MSOs)
24 also have a commercial interest in limiting access to these premium services to
25 authorized users only.

26 Subscribers receive digital broadcasts (including satellite, cable and Web
27 broadcasts) via Set-Top Boxes or other similar consumer electronic equipment
28 located in the subscriber's home. With a bi-directional Set-Top Box, in addition to
29 receiving broadcasts, a subscriber can transmit messages to the MSO. Using the
30 bi-directional Set-Top Box (generally, a "transceiver" or "intelligent transceiver"), the

1 subscriber selects a premium service, and the subscriber's selection as well as
2 information needed for billing purposes is transmitted to the MSO. In a common
3 implementation, a "smart card" may be used to store the information needed for
4 billing, and on a periodic basis (perhaps once per month) an automatic connection
5 is made between the transceiver and the MSO so that the billing information can
6 be transmitted to the MSO. In other implementations, a Point of Deployment
7 module (POD) is used without such a smart card, to enable all conditional access
8 functions. In still another embodiment, the POD is used to carry out all conditional
9 access functions in cooperation with a smart card interconnected therewith as a
10 repository for key codes used in the conditional access structure.

11 Digital broadcast content is vulnerable to unauthorized use and duplication
12 ("pirating") while it is being broadcast, or after it has been received and is being
13 processed. For example, during broadcast, the signal could be intercepted and
14 displayed (or duplicated and rebroadcast) using a transceiver not provided by the
15 MSO. On the other hand, even when a transceiver provided by the MSO is used,
16 the signal could be diverted within the transceiver so that the conditional access
17 functions are bypassed. In either case, copyrights are circumvented. In addition,
18 the MSO is unaware of the unauthorized use and so does not have the information
19 needed to collect the fees it is owed. To prevent such unauthorized use, MSOs
20 typically broadcast a scrambled signal. The signal is descrambled in the
21 transceiver using a key generated by a processor in the STB in cooperation with the
22 smart card. A new key may be generated periodically by the MSO, so that when
23 new key data are received, the STB processor generates a new key using key data
24 received from the MSO in cooperation with the smart card.

25 While the present invention is described in conjunction with an embodiment
26 of an OpenCable™ compliant television Set-Top Box, this should not be considered
27 limiting since the invention could equally well be implemented within a digital
28 television (DTV), television receiver, television, game console (e.g., the PlayStation
29 series of game consoles from available from Sony Corporation, Tokyo, Japan), a
30 Personal Information Manager or any other suitable receiver or transceiver system.

Turning now to **FIGURE 1**, block diagram 100 shows some of the elements in one embodiment of a system for transmission and receipt of a digital broadcast signal in a cable television system consistent with one embodiment of the present invention. In system 100, an MSO 110 broadcasts programming through a cable network 120 to a Set-Top Box 130 for display on a television monitor 140. In this embodiment, Set-Top Box 150 includes POD card 150 which, in this embodiment, accepts a smart card 160. In other embodiments, smart card 160 may be interfaced directly to the STB 150, rather than the POD card 150, by insertion of the smart card 150 into a smart card slot forming a part of the STB 150. Either embodiment is equivalent for purposes of the present invention. In a system which is OpenCable™ compliant, POD card 150 provides all of the conditional access system components within a single PCMCIA module.

In this embodiment, the POD card 150 alone or in combination with the smart card, is used to provide all conditional access functions for the Set-Top Box 130. The smart card 160 is used (alone or in cooperation with a processor) to generate decryption keys used for descrambling broadcasts and decrypting programming that has been appropriately paid for by the user and to provide billing information to the MSO 110. Those skilled in the art will appreciate that the diagram 100, while depicting the interconnectivity of the POD card 150, the STB 130 and the smart card 160, is intended to be merely illustrative, and is not intended to be a scaled mechanical representation of these components. In the OpenCable™ standard, the POD card 150 or the POD card 150 in cooperation with a smart card, operate to carry out the function described as a "security module". The OpenCable™ standard POD module is described in "OpenCable™ Architecture" by Michael Adams, 2000, Cisco Press, pp 380-400 which is incorporated herein by reference.

Those skilled in the art will appreciate that the video and audio information that make up the program content may be encoded using various digital encoding techniques (e.g., MPEG) to produce data streams that represent the video and audio information. The term "data stream" or "video data stream", as used herein,

1 generally refers to such a digitally encoded stream of information. The stream of
2 information, while often referred to as a "video stream", may have video, audio and
3 other elemental streams. Those skilled in the art will understand from the context
4 when a data stream referred to as a "video stream" may also contain audio
5 elemental components as well as other information, as previously explained.
6 Moreover, while the present invention may be particularly suitable for recording of
7 audio/video (A/V) content, the present invention is not to be considered limited by
8 such since other data (e.g., fax, web content, other data streams, email, etc.) could
9 equally well be stored using the techniques described herein without departing
10 from the invention.

11 **FIGURE 2** shows the exemplary Set-Top Box 130 and associated POD card
12 150 in greater detail to illustrate the conditional access functions carried out in the
13 POD card 150 as well as the PC card recorder of the present invention. For clarity,
14 not all of the elements of the Set-Top Box 130 or POD card 150 are shown in this
15 illustration. POD card 150, as illustrated, may or may not operate in cooperation
16 with a smart card 160 as depicted in block diagram 100, depending upon the
17 desired implementation.

18 Front-end unit 204 of the Set-Top Box 130 includes a tuner (not shown), as
19 well as other devices known in the art (e.g., analog-to-digital converter, oscillator,
20 QPSK demodulator, etc.), for receiving a digital broadcast signal from the cable
21 system at 208. Coupled to front-end unit 204 is point of deployment (POD) module
22 150, coupled through a POD interface 212, which in accordance with certain
23 preferred embodiments, is a PCMCIA compliant interface. POD 150 may be (but
24 is not necessarily) adapted to receive smart card 160 (not shown) that, as
25 described above, can be used to provide billing information to the MSO 110. In
26 other embodiments, smart card 160 may directly interface with the STB 130. The
27 smart card 160 also typically contains information needed to generate decryption
28 keys upon receipt of certain key information provided by the MSO 110. Such
29 decryption keys when generated are used to descramble the digital broadcast
30 signal at 208.

1 POD 150 includes an encryption block 214 and a decryption block 218.
2 Decryption block 218 uses the key provided by the MSO 110 to descramble the
3 broadcast signal at 220 (if the signal is scrambled). Encryption block 214 also
4 encrypts the signal (if the signal is not encrypted). Connection 220 forms a part of
5 a PCMCIA interface in accordance with certain preferred embodiments.

6 Set-Top Box 130 also includes a decryption block 224 for decrypting an
7 encrypted broadcast signal received from front-end 208 before the signal is
8 demultiplexed by the transport parser/demultiplexer 230 and sent to audio decoder
9 234 and video decoder 240. These decoders 240 and 234 are used for decoding,
10 for example, MPEG (Moving Picture Experts Group) video signals and/or Dolby AC3
11 audio signals. The decoded signals are provided at suitable outputs 242 and 246
12 to drive other A/V equipment such as a television receiver. The output signals at
13 242 and 246 may be in any suitable format for driving A/V equipment including S-
14 Video format, PAL format, component video format, NTSC format, analog audio,
15 composite video, etc. In some embodiments, the output signals at 242 and 246
16 may be combined and modulated to a standard television frequency without
17 departing from the present invention.

18 Front-end block 204 demodulates and error-corrects a data stream from the
19 MSO 110. When no POD is inserted, switch 284 in POD interface 212 is closed.
20 The output stream from front-end 204 is sent to decrypter 224 through switch 284.
21 Decrypter 224 decrypts the stream and sends it to transport parser/demultiplexer
22 230. The stream is demultiplexed at the TP/demultiplexer 230 so that video data
23 is appropriately sent to video decoder 240 and audio data is appropriately sent to
24 audio decoder 234. Other information may be demultiplexed at TP/demultiplexer
25 230 for CPU 250, and is supplied thereto over the system bus 266. The outputs
26 from the two decoders 234 and 240 are sent to the TV set.

27 User Interface 260 receives an infrared command from remote commander
28 256 and sends it to Host CPU 250 through PCI Bus 266. All the blocks heretofore
29 described within STB 130 are controlled by Host CPU 250 over PCI Bus 266. Host

1 CPU 250 includes non-volatile and/or volatile memory (not shown) for the software
2 code, working area and temporary data storage operating in a known manner.

3 Once POD card 150 is inserted to the POD slot of the STB 150, POD
4 interface 212 detects it and informs the host CPU 250 via the system bus 266.
5 Host CPU 250 opens switch 284 in response by sending a command to the POD
6 interface 212 via the system bus 266. The data from the front-end 208 is thus
7 diverted to the POD card 150 and is decrypted by decrypter 218 and re-encrypted
8 by encrypter 214. The re-encrypted data stream goes to decrypter 224 through the
9 POD interface 212. The data stream is processed in decrypter 224 and the blocks
10 after decrypter 224 (blocks 230, 234 and 240) in the same way as when no POD
11 150 is inserted. Decrypter 218 and encrypter 214 are controlled by the embedded
12 CPU 270 over local bus 274.

13 CPU 270 also includes volatile and/or non-volatile memory (not shown) for
14 software code storage, working area and temporary data storage. CPU 270
15 communicates with Host CPU 250 through the POD interface 212 and bus
16 interface 280. The software code in CPU 270 is preferably stored in non-volatile
17 memory and is downloadable to permit updating. Front-end 208 receives the
18 software code from the head end of the cable system. Host CPU 250 transfers the
19 code to CPU 270 using the system bus 266, the POD interface 212 and the bus
20 interface 280. CPU 270 also sends back upstream data to front-end 204 through
21 bus interface 280 and POD interface 212. Front-end 204 receives the data and
22 sends back the upstream data to the head end. The upstream data may include,
23 for example, pay-per-view charge information. The details of POD copy protection
24 are discussed in the OpenCable™ POD Copy Protection System specification
25 which can be obtained from <http://www.scmicrosystems.com/dvb/pod.html>).

26 The encryption method used for the stream sent from the head end of the
27 cable system is dependent upon the particular MSO. Usually, the encryption
28 method is not open to public. The specification of decrypter 218 is also generally
29 a secret to protect the integrity of content from copying. Encrypter 214 of the
30 certain embodiments encrypts the data stream using DES-ECB mode encryption

1 as described in the text "Applied Cryptography", by Bruce Schneier (John Wiley &
2 Sons, Inc. ISBN 0 -471-11709-9). Information on the DES standard can be found
3 in FIPS PUB 46-1, 46-2, "Specification for the Data Encryption Standard", National
4 Institute of Standards and Technology; FIPS PUB 74, "Guidelines for Implementing
5 and Using NBS DES", National Institute of Standards and Technology; and FIPS
6 PUB 81, "DES Mode of Operation", National Institute of Standards and Technology.

7 By using a POD card such as 150, each MSO can use its own encryption method
8 to encrypt their data streams. The user can use the same STB even when he/she
9 moves to another MSO's service area by simply obtaining a new POD card 150
10 from the new MSO and inserting it to the POD card connector (generally a standard
11 PCMCIA connector) of their STB. The Federal Communication Commission is
12 requiring that all the cable STBs have a POD slot by the year 2005 to permit such
13 transportability of STBs.

14 Thus, as described above, digital broadcast signals at 208 are received by
15 the Set-Top Box 130 at front-end 204 and forwarded to POD 150. The broadcast
16 signal at 220 is descrambled by decryption block 218. Once descrambled, the
17 broadcast signal is encrypted at 214 to prevent unauthorized duplication. Further
18 downstream in the Set-Top Box 130, the broadcast signal is decrypted using
19 decryption block 224 so that it can be decoded (e.g., MPEG or AC3 decoding) in
20 decoders 234 and 240, and subsequently processed so that it can be viewed
21 and/or listened to by an authorized subscriber. These activities are carried out in
22 cooperation with a host CPU 250 upon receipt of control instructions from a user,
23 for example, via commands from a remote commander 256 communicating with
24 a user interface 260 of Set-Top Box 130, e.g., via infrared communication. The
25 various component blocks of the Set-Top Box 130 may communicate using one or
26 more bus structures such as a PCI bus shown as system bus 266. Similarly, POD
27 card 150 operates under control of a supervisory CPU 270 that communicates with
28 the encrypter 214 and decrypter 218 via its local bus 274 and communicates with
29 the host CPU 250 via bus interface 280 connected through the POD interface 212
30 to PCI bus 266.

1 The present invention utilizes a memory device, preferably a solid state non-
2 volatile memory, forming a part of the POD card 150 to provide the functionality of
3 a recorder for storing programming. The current embodiment is especially suitable
4 for short time recording and playback. As the state of the art progresses in
5 production of solid state memory, large storage times should be achievable without
6 use of HDDs. Until then, the POD card with memory can be used for short time
7 recording or short time-shift purposes (i.e., instant replay and short time shifts).
8 256 Mbytes of memory can be used to record a 4 Mbit/sec (bps) program for
9 approximately 8.5 minutes. As the cost of memory declines, it is anticipated that
10 several Gbytes will be an affordable alternative to HDD technology in the present
11 invention, making it suitable for replacement of HDD technology. Such advances
12 will undoubtedly soon make two or more hours of recording possible using solid
13 state memory. The additional circuitry that achieves the storage of programming
14 on the POD card 150 is illustrated in **FIGURE 3**. The term "PC card" as used herein
15 is intended to have the conventional meaning of a computer device having any of
16 the current or future PCMCIA compliant dimensions, connector and interface.

17 The present PC card recorder provides for using the POD as storage device
18 by adding memory and memory control circuitry. This is accomplished while
19 retaining the POD copy protection functions. POD copy protection is described in
20 the OpenCable™ HOST-POD Interface Specification which can be downloaded
21 from <http://www.scmmicrosystems.com/dvb/pod.html>, and OpenCable™ POD Copy
22 Protection System which is available to be downloaded from
23 <http://www.scmmicrosystems.com/dvb/pod.html>. The card size is preferably fully
24 compliant with the PC card standard described in PC Card Standard 7.4 which
25 can be downloaded from <http://www.pc-card.com/>, and "PCMCIA System
26 Architecture" by Don Anderson, Addison-Wesley Pub Co; ISBN: 0201409917. The
27 connector interface is preferably the same as the OpenCable™ Point Of
28 Deployment (POD) card. No special interface like iLINK or IDE is required. In order
29 to use the PC card recorder of the present invention, the user simply inserts the PC
30 card recorder into the existing POD slot.

1 In the embodiment shown in **FIGURE 3**, the PC card recorder is shown as
2 350. The data stream sent from decrypter 218 is parsed in transport parser/packet
3 filter 354 and program information is extracted. The program information is sent to
4 the host CPU 250 through CPU 270, bus interface 280 and POD interface 212.
5 Based on the program information, host CPU 250 generates a program table and
6 displays it on the TV screen using the graphic display capability of the video
7 decoder 240. The user chooses a program he or she wants to see using remote
8 commander 256. User interface 260 receives a command from remote
9 commander 260 and sends it to host CPU 250. Host CPU 250 informs CPU 270
10 of the PID (Packet Identifier) numbers of the program the user choses. CPU 270
11 commands TP/P.filter 354 to pass only the specified packets having the selected
12 packet identifier. All the other unnecessary packets (packets not related to the
13 selected program) are dropped here. By way of example, the data rate of the
14 original data stream at the input of the TP/P.filter 354 is generally about 40Mbit/sec
15 in the case of 256 QAM (Quadrature Amplitude Modulation) cable transmission.
16 After filtering at TP/P.filter 354, the rate is reduced to approximately 4Mbit/sec.
17 TP/P.filter 354 also modifies the program information , re-packetizes it and inserts
18 it into the stream.

19 A memory interface 358 receives the partial data stream (i.e., the filtered
20 data stream) from the TP/P.filter 354 and time-stamps each packet using time
21 information from a reference clock 362. The time stamp may be, for example, a 32-
22 bit value that is added to each packet. A 32 bit clock value yields a time resolution
23 of 10 microseconds. A 32 bit clock permits 700 minutes of recording time ((2^{32})
24 $\times 10 \text{ usec} > 700 \text{ min.}$). This is long enough for several hours of recording time.
25 If additional recording time is to be accommodated, more bits can be allocated to
26 the time stamp. Time-stamped packets are sent from memory interface for storage
27 in memory 370. Memory 370 is preferably made up of non-volatile solid state
28 memory such as Flash memory, but this is not to be considered limiting since other
29 forms of storage may also be suitable. At the time of playback, the time stamp
30 value is compared with the reference clock in the memory interface 358. When the

1 stamped time comes, the time-stamp is removed from the packet and the packet
2 is dispatched to encrypter 214 and then to the decrypter 224 for playback. The time
3 stamp system retains each time gap between packets.

4 When the user specifies a record or playback mode from remote
5 commander 256, the host CPU 250 receives the command through the user
6 interface 260 and sends a corresponding command to CPU 270. CPU 270 controls
7 memory interface 358 to move a write pointer and/or a read pointer in memory 370,
8 to control the write and read operations as will be described later.

9 TP/P.filter 354 has packet marking capability for use in carrying out special
10 operations referred to herein as "trick mode" operations. A special packet or data
11 can be inserted at the top of certain types of pictures, for example, MPEG (Moving
12 Pictures Expert Group) intra coded pictures as described in ISO-IEC 13818
13 International Standard for the Transport of Compressed Digital Media (MPEG).
14 This provides the STB 130 to provide intra picture only playback to produce a fast-
15 forward effect. Marked packets can be selected by the TP/demultiplexer 230 which
16 can discard other packets until the next marker is found. Also, CPU 270 can create
17 a table of starting and ending addresses of Intra pictures by using the TP/P.filter
18 354 to parse the data stream. Based on this table, CPU 270 commands the
19 memory interface 358 to successively move the read pointer from one intra picture
20 to the next one after another. This provides efficient memory access for smooth
21 fast-forward playback. This process is described in additional detail in connection
22 with **FIGURE 8**.

23 In one embodiment, a packet header can be added to the top of each packet
24 with the header containing a time stamp and an identifier that can be used to
25 identify the various packet types (e.g., I-picture packets). In this embodiment, the
26 TP/P.filter 354 parses each packet. When a parsed packet is the top of an I-picture
27 or the end of an I-picture (or top of the next picture), TP/P filter 354 sets an I-picture
28 top (or end) indicator in an additional header for the packet. The packet is stored
29 with this additional header. In fast-forward mode, all the time stamps are ignored.
30 The packets stored in memory 370 are read successively. Memory interface 358

1 detects the I-picture atop and end flags and sends only I-picture packets to
2 encrypter 214. Only I-picture packets are sent to STB 130. TP/Demux 230 does
3 not have to parse packets again to get I-picture data.
4

5 **FIGURE 4**, which includes **FIGURES 4A-4F**, shows how the data is written
6 to and read from the memory 370, often simultaneously, by use of the read and
7 write pointers under various circumstances. When the write or read pointer
8 reaches the last address of memory 370, it returns to the first address. Therefore,
9 the pointers can be shown as clockwise moving points on a circle, and the memory
10 can be considered to be a circularly arranged memory.

11 For long recording times, conventional memory management techniques
12 can be used to manage access to the memory 370. In one embodiment, CPU 270
13 manages all accesses to the memory with a small portion of the memory allocated
14 for short time delay functions. The remaining area is used for longer recording
15 functions. CPU 270 manages the recording area to minimize fragmentation and
16 carry out other memory management functions.

17 The recording operation is discussed with reference to **FIGURE 4A**. The
18 write pointer (WP) starts at the starting point (SP), which is the first address of
19 memory 370. The bold arc spanning SP to WP indicates a written area that has
20 not yet been read. When recording begins, for example as a result of a user
21 command using remote commander 256, the write pointer WP is advanced
22 clockwise as the program is recorded to memory 370. In the case of a small
23 memory embodiment (i.e., only enough memory for a few minutes of recording
24 time), recording may begin whenever a user selects a program so that live replay
25 functions can be provided. In that case, the memory 370 is used as a cache for
26 incoming programming to allow for repeat play. In other embodiments, a small
27 amount of memory can be set aside (i.e., one minutes worth of recording time) as
28 a cache (configured as circular memory) that is always recording the currently
29 viewed programming.

1 In certain embodiments, a specified area of memory 370 is used to handle
2 short time delay functions (e.g., five minutes worth of memory). This specified area
3 of the memory 370 is overwritten repeatedly. The other area of memory 370 is
4 used for longer recordings. When creating a long recording, if necessary, the user
5 can pause or delay playback similar to the same functions as described for short
6 time delays. But, different areas of storage are used. In this embodiment, the user
7 specifies whether long or short term recording is to be used before recording.
8 Using short time recording in this manner does not guarantee that the information
9 will not be overwritten. Other embodiments will also occur to those skilled in the
10 art.

11 When playback begins, the read pointer (RP) starts reading with SP as
12 illustrated in **FIGURE 4B**. In the normal playback mode, both WP and RP proceed
13 at approximately the same speed. More precisely, the write rate and the read rate
14 may not be identical. There is generally a range of drifting because the stream is
15 usually encoded at variable rate. However, the average rate is fixed. Therefore,
16 WP and RP keep approximately the same distance over a long time period. Thus,
17 RP never catches up with WP. In this mode, the user is essentially time shifting
18 live programming. That is, for example, if the distance in time between RP and WP
19 is two minutes, (i.e., using short term recording) the user is viewing the
20 programming that was broadcast live two minutes prior. Similarly, generally for
21 long term recording using a larger memory, the writing may correspond to recording
22 a program being currently broadcast, while the reading may correspond to viewing
23 a program that was recorded days earlier.

24 In another time-shifting operation, the user issues a pause instruction at a
25 time corresponding to X from remote commander 256. The read pointer RP stops
26 at point X in **FIGURE 4C**, but the write pointer WP keeps moving ahead. When the
27 user re-starts decoding (playback), for example by issuing a "play" command from
28 remote commander 256, the read pointer RP begins advancing. The maximum
29 time-shift period is essentially the amount of record time that can be stored in the

1 memory 370. In the case of a memory that contains protected information (i.e., a
2 program stored for later viewing), the maximum time shift period corresponds to the
3 amount of free memory in memory 370.

4 Especially in the case of systems able to store large amounts of data, it is
5 desirable to be able to preserve stored programming for long periods of time. Thus,
6 it is desirable that the user should have to explicitly issue an erase instruction
7 before overwriting such recordings. The details of programming such functions are
8 within the ordinary skill in the art given the present disclosure.

9 The present invention, in certain embodiments, provides the ability to catch
10 up with the current broadcast by use of a "catch-up" mode of play. Such operation
11 is desirable, for example, if a viewer has to leave the room for a brief period of time
12 and wishes to pause a live broadcast and then return to viewing it. The catch-up
13 mode is similar to the time-shift mode in that reading and writing are carried out
14 simultaneously with the read pointer RP lagging the write pointer in time. But in the
15 catch-up mode, by dropping certain pictures, RP is advanced faster than WP so
16 that it eventually catches up with WP. Time stamps are ignored in this mode since
17 the dropping of certain pictures results in a desired timing difference that shortens
18 playback time versus record time. For example, several bi-directional pictures
19 (MPEG B-Pictures) in a GOP (Group of Pictures) may be dropped by
20 TP/demultiplexer 230. In one embodiment all such bi-directional pictures are
21 dropped. In another embodiment, one (e.g., the first) bi-directional picture, if
22 present, is dropped from each GOP. In other embodiments, varying numbers of bi-
23 directional pictures can be dropped from a GOP (e.g., one from each third GOP
24 with B-Pictures, or three from each GOP having B-Pictures). The more such bi-
25 directional pictures are dropped, the faster RP advances toward WP, but dropping
26 large numbers of bi-directional pictures may result in noticeable loss of picture
27 smoothness. Accordingly, it may be desirable to provide the user with an ability to
28 select, e.g., using remote commander 256, a catch up speed. In such an
29 embodiment, catch-up speed control commands from the remote commander
30 correspond to numbers of bi-directional pictures that can be dropped. The user

1 can, thus, balance the catch-up speed against desired picture smoothness. Bi-
2 directional pictures are selected for this process since they depend, at least in part,
3 on both prior and future pictures. Thus, much of the information in a B-Picture will
4 be obtained from other pictures (MPEG I-Pictures or P-Pictures).

5 During the catch-up mode of operation, the data are read intermittently from
6 memory 370 as a result of a request from TP/demultiplexer 230, possibly based
7 upon the number of bi-directional pictures to be dropped. Preferably, a small
8 number of pictures are dropped to disguise this playback as a normal playback.
9 The dropped pictures cause RP to advance a little faster than WP. Thus, RP
10 eventually catches up with WP. After catching up, the mode switches to a normal
11 playback mode. In this manner, the user can catch up to a current time of a
12 program currently being broadcast without unacceptable loss of picture
13 smoothness.

14 During the various playback modes, the playback speed can be controlled
15 as follows, in certain embodiments. In normal playback mode, the each packet is
16 dispatched to the A/V decoder based on time stamp so that the A/V decoder buffer
17 will not overflow or underflow. In trick play modes, the time stamp is ignored.
18 Packets are sent to the A/V decoder one after the other in rapid succession. When
19 the buffer fills, the reading from memory pauses until the A/V decoder reads data
20 from the buffer and frees enough buffer space to accept more data. The pause
21 period varies according to the mode. The pause is short in fast forward or rewind
22 mode and slow in slow motion mode.

23 The present invention also contemplates a fast forward mode. In this mode,
24 data from memory 370 are read ignoring time stamps. The TP/demultiplexer 230
25 captures and decodes only Intra pictures (i.e., MPEG I-Pictures). Intra pictures do
26 not depend on other pictures (other MPEG I-Pictures, B-Pictures or P-Pictures) for
27 any of their information. Since each MPEG GOP contains an Intra picture, this
28 provides a handy way to present a representation of the group of pictures as a fast
29 forward mechanism.

1 In normally encoded MPEG video, the type of picture (I, B or P) is
2 conventionally determined by analysis of the data to make a determination as to the
3 picture type. In order to enhance the ability to provide fast forward and other
4 operations, the present invention contemplates making a determination of a picture
5 type at the time of recording and storing this information either in a table or as a
6 packet attribute in a packet header.

7 The data stream from memory 370 stops and goes frequently by request of
8 TP/demultiplexer 230 as the I-Pictures are retrieved without retrieving any of the
9 other pictures stored in memory 370. The read pointer RP thus jumps from one I-
10 Picture address to another and advances substantially faster than WP. Eventually,
11 RP catches up with WP as shown in **FIGURE 4D**. RP stops just before WP and
12 the mode is switched to normal playback mode if requested.

13 As described earlier, by using an intra picture address table,
14 TP/demultiplexer 230 can easily find the top of each of the Intra pictures. In this
15 case, RP directly jumps to the top address listed in the table. When RP reaches
16 the end address, it jumps to the next top address as specified in the intra picture
17 address table. Thus, only intra picture data is sent to STB 130 for decryption,
18 decoding and playback. This mode is described in additional detail in connection
19 with **FIGURES 8-9**. Information regarding B and P pictures can also be tabulated
20 to facilitate other modes of operation.

21 The present invention also contemplates a "repeat" mode of operation
22 similar to an instant replay feature. **FIGURE 4E** illustrates the repeat mode. WP
23 stops. RP jumps back to a preceding memory location Y and starts reading from
24 there again. RP stops at a memory location just before the write pointer WP. The
25 user may playback the sequence over and over again, in which case, RP
26 repeatedly jumps to Y.

27 In another embodiment, wp does not stop, but continues advancing so the
28 viewer doesn't lose programming while repeating. The point at which the
29 command is issued can be stored to form a starting point for the repeat. For

1 example, if the viewer issues another repeat command within 1 minute, the same
2 image is repeated again. Then, the viewer could enter the catch-up mode and not
3 miss any programming. In this case, wp advances in a controlled manner so as
4 not to overwrite a recorded area that has not yet been read.

5 Backward play at slow and fast speed can be possible by using the
6 technique described in U.S. Patent No. 5,715,354, entitled "Image data
7 regenerating apparatus" to Iwamura et al. which describes an MPEG video
8 backward play method using an optical video disc as a storage and is hereby
9 incorporated by reference. This same method can be applied to solid state
10 memory such as memory 370.

11 **FIGURE 5** illustrates another embodiment of the PC card recorder and STB
12 arrangement consistent with the invention in which a second PC card can be
13 added. In this embodiment, the user can, for example, time-shift one program to
14 the first PC card recorder while recording another. In this embodiment, Set-Top
15 Box 530 has two front-end units 208A and 208B. STB 530 also has two POD
16 interfaces 212A and 212B receiving data streams respectively from the front-end
17 units 208A and 208B. PC card recorders 350A and 350B (or other POD devices)
18 are inserted to each of the POD interfaces respectively. The two PC card recorders
19 can thus be configured to record different programs under the control of host CPU
20 250. For example, Front-end 208A can be tuned to one program where the
21 program is time-shifted by PC Card Recorder 350A. The time shifted program is
22 sent to decrypter 224 through a switch 520, which is configured to connect the data
23 stream from POD interface 212A connects to the decrypter 224. Thus, the program
24 being processed by PC card recorder 350A is available for the user to watch.

25 Meanwhile, Front-end 208B can be tuned to a second program. PC card
26 recorder 350B can be configured under control of host CPU 250 to record the data
27 stream from front-end 208B. When the user wants to watch the second program,
28 he or she simply changes the program source, e.g., by using a source switch
29 button on remote commander 256. The command is received by host CPU 250
30 through user interface 260. Host CPU 250, in response to the command, changes

1 the setting of switch 520 to connect a data stream from POD interface 212B to the
2 decrypter 224. The program recorded in PC card recorder 350B is thereby
3 decoded. In another embodiment, the STB 530 can be provided with a second
4 decrypter such as 224 and TP/demultiplexer such as 230. In this embodiment, the
5 two data streams from both PC card recorders can be decoded simultaneously.
6 In this embodiment, as will be clear to those skilled in the art, the STB 530 can also
7 accommodate one PC card recorder and one POD. The signals at 208A may
8 originate at the same cable connection or may be supplied from different sources
9 without departing from the invention.

10 The structure described above provides not only for enhanced storage and
11 playback of video, but also provides a greater level of security. Compared with a
12 Hard Disc Drive, a PC card is less vulnerable to reverse-engineering. The card is
13 sealed in a manner that makes it difficult to open without damage. This makes is
14 more difficult to appropriate an unencrypted digital video stream, and thus breech
15 conditional access and copyright. Moreover, since the present PC card recorder
16 internally has a decrypter 218 and an encrypter 214, and since the decryption and
17 the encryption algorithms are fully under the MSO's control, the information stored
18 in the PC card recorder is not useful outside the system under the control of the
19 MSO. By downloading new software and/or encryption/decryption keys to each
20 STB, the MSO can freely change encryption/decryption algorithm at minimum cost.
21 Thus, this system provides maximum security to the PC card recorder.

22 In order to further enhance security in the present system, the PC card
23 recorder shown in **FIGURE 6** as 650 can be utilized. In this embodiment, the data
24 stream may be encrypted before being written to memory 370 and decrypted after
25 being read from the memory 370. In one embodiment incorporating such
26 encryption, an encrypter 610 is placed between TP/P.filter 354 and memory
27 interface 358 to encrypt data before it is written to memory 370. In a similar
28 manner, a decrypter 620 can be placed between memory interface 358 and
29 encrypter 214. This encryption gives more security to the PC card recorder, since
30 there is no data stored "in the clear." Moreover, different encryption / decryption

1 algorithms can be used in encrypter 610 and decrypter 620 than used in encrypter
2 214 and decrypter 218 to further thwart attempts to access the data in memory 370.
3 If the encrypter 610 and decrypter 620 are integrated within memory interface 358
4 and 214 respectively, the areas wherein clear program content is available is further
5 limited.

6 For content protection, the particular PC card recorder recorded with a
7 particular STB should preferably be usable with only one STB. That is, content
8 recorded on a particular STB should preferably only be capable of playback on the
9 same STB. This is referred to as pairing security and further limits any attempts to
10 misappropriate content. The present PC card recorder can, in certain
11 embodiments, provide pairing security to help assure this is the case. The STB 130
12 has its own unique ID number, for example stored inside host CPU 250. The
13 number cannot be readily read out of the STB. In one embodiment, when
14 recording, the PC card recorder 350 reads this number and stores it in the non-
15 volatile memory associated with CPU 270. When a playback command is
16 received, the PC card recorder reads the number from the STB 130 and compares
17 it to the stored number. If the number is are identical to the number PC card 350,
18 playback starts. If not, playback is prohibited because the STB is not the same one
19 used for recording. The unique ID number may be encrypted before being sent to
20 the PC card recorder 350 and decrypted by CPU 270 to protect the system from
21 unauthorized theft of the content stored in the PC card recorder 350. Equivalently,
22 other information exchanges can be made and compared to assure that the
23 recording STB is the same as the playback STB.

24 The pairing security feature of the preferred embodiment is illustrated in
25 **FIGURE 7** as process 700 starting at 702. In the event the user wishes to initiate
26 recording at 706 by issuing a command from remote controller 256, the PC card
27 CPU 270 obtains an encrypted Set-Top Box number from the host CPU 250 at 710.
28 The STB number (or other appropriate information) is stored in nonvolatile memory
29 (e.g., memory associated with CPU 270) at 712 and the program is recorded at
30 716. When the user issues a playback command at 720, the PC card CPU 270

again obtains an encrypted STB number from the hosts CPU 250 at 724. This STB number is decrypted at 728. The stored STB number is decrypted at 732 and the two numbers are compared at 736. If they are the same at 740, the programming is played back at 744 and control returns to 706. If they were not the same, however, the playback is rejected at 748 and an error message is issued at 756 notifying the user is that playback is not possible since of the programming was recorded with a different Set-Top Box. While this embodiment is described in terms of a Set-Top Box number, it can equivalently be realized using any information that can be used by the PC card to authenticate the STB.

As previously discussed, the present invention can provide trick mode operations such as an intra picture only playback. This technique is applicable to MPEG encoded digital video signals wherein intra-coded pictures (I-Pictures), as distinguished from inter-coded pictures such as predictive coded pictures (P-Pictures) and bidirectional Predicted Pictures (B-Pictures) make up a group of pictures (GOP). The record process used to provide intra picture only playback is illustrated in **FIGURE 8** as process 800 starting at 802. This process is carried out within the PC card recorder by the TP/P.filter 354 in cooperation with CPU 270, memory interface 358 and memory 370. At 806 a new packet of MPEG data is received at TP/P.filter 354, and the packet is stored to memory 370 by the memory interface 358 at 810. If the new packet represents the start of an intra picture at 816, as determined by the TP/P.filter 354 or CPU 270, the start address for the memory location storing the packet is added to an intra picture address table by CPU 270 at 820. Control then passes to 830. If not, control passes to 840 where it is determined by TP/P.filter 354 if the packet represents the end of the intra picture data. If so, the address of the memory location storing this packet is added to the intra picture table at 844 by CPU 270. If not, control passes to 830 to determine if the end of the program has been reached. If not, control returns to 806. When the end of the program is reached, the process ends at 836. The intra picture table can be stored in memory 370 or, alternatively, in memory associated with the CPU 270. **TABLE 1** below generally represents the information stored in

1 the intra picture address table. The Packet Identifier (PID) determines the
2 association of the packet with a particular program.

PID	INTRA START ADDRESS	INTRA END ADDRESS
0x10	sector 0x00110000	sector 0x00112000
0x10	sector 0x00150000	sector 0x00153000
...

7 **TABLE 1**

8
9 Playback of the program using the intra picture mode can be accomplished
10 by process 900 of **FIGURE 9** starting at 902. At 906 if the intra picture mode is not
11 selected, normal playback (or other mode of playback handling) is carried out at
12 910. In the event intra picture playback mode is selected at 906, the start address
13 and end address in memory 370 for a first picture is read from the intra picture
14 address table by CPU 270 at 914. The read pointer of memory 370 is then moved
15 to the start address by memory interface 358 and data is read through the intra
16 picture end address at 918 by memory interface 358 under control CPU 270. The
17 memory interface 358 sends the information read from memory 370 to encrypter
18 214 where the information is encrypted.

19 The encrypted information is sent to the STB decrypter 224 through the POD
20 interface 212. The decryption, decoding and playback of the picture is then carried
21 out within the STB using encrypter 224, TP/demultiplexer 230 and video decoder
22 240 at 934. Simultaneously, in the PC card recorder, CPU 270 determines at 938
23 if the start and end addresses represent the last address pair in the current
24 program at 938 (either by reference to the intra address table's PID entry or by
25 reading a PID stored with the next intra address pair. If the last address pair has
26 been read, the process ends at 944. If not, the next address pair location in the
27 intra picture address table is incremented at 950 and control returns to 914 where
28 the next start and end address is retrieved from the intra picture address table.

1 Referring now to **FIGURE 10**, an alternative embodiment of a PC card
2 recorder 1050 having either record-only mode or short time-shift mode is illustrated.
3 In this embodiment, block 354 of **FIGURE 3** (or **FIGURE 6**) is replaced with a
4 packet filter 1054 without a transport parser. In this embodiment, the
5 TP/demultiplexer 230 of the STB 130 parses the program information and the host
6 CPU 250 communicates with CPU 270 to have CPU 270 command block 354 to
7 drop unnecessary packets. In this embodiment, TP/demultiplexer 230 obtains the
8 newest program information from the input stream. In record-only mode, memory
9 interface 358 sends the input stream both to memory 370 and to encrypter 214.
10 The encrypted data stream from encrypter 214 is sent to TP/demultiplexer 230
11 through decrypter 224.

12 In long time-shift mode, for example, in 1-hour delayed playback, the
13 program specific information in the program specific information tables (e.g.,
14 MPEG PAT table, PMT table, etc.) might have changed. Thus, the most current
15 program specific information tables may not accurately reflect the program
16 information stored in memory 370. In order to avoid use of an erroneous program
17 specific information table, the tables in their form at the time of recording, are
18 stored within a memory location provided in the packet filter 1054. Thus, in the
19 current example, for playback, the TP/demultiplexer 230 obtains the 1-hour old
20 program information, which would differ from the current program information, from
21 packet filter 1054 in order to play back the stored program. In other embodiments,
22 the program specific information tables can be stored with the program in memory
23 370 or in any other suitable storage location without departing from the present
24 invention. In other embodiments, the encryption arrangement as illustrated in
25 **FIGURE 6** can be incorporated in the PC card recorder 1050.

26 In another embodiment of the present invention, the recorder functions can
27 be implemented in a non-OpenCable™ compliant card. Similarly, decryption and
28 encryption in 218 and 214 are not required to be OpenCable™ compliant.
29 Additionally, other types of cards (for example, a smart card) can be used to

1 embody a recorder consistent with the present invention. The various functions of
2 the card (e.g., encryption, decryption, memory management, filtering functions,
3 etc.) can be carried out using dedicated hardware, one or more programmed
4 processors or a combination thereof without departing from the invention.

5 The PC card recorder of the present invention has the advantages of being
6 small and mechanically robust. Upgrades are easy by simply changing the PC
7 card. The invention provides good performance for short time shift or short
8 playback operations. No dedicated hardware interface required since the existing
9 POD slot is used. The data stored in the memory is secure (POD copy protection
10 compliant. Card-STB pairing security) and flexible (since by software download,
11 decryption and re-encryption can be modified, and software bugs can be easily
12 fixed). The arrangement is easily expandable by use of a second card as illustrated
13 in the embodiment of **FIGURE 5**.

14 The embodiments described utilize dedicated hardware encryption and
15 decryption processors as preferred embodiments. However, those skilled in the art
16 will recognize that encryption and decryption can equivalently be carried out in
17 software using a suitably programmed processor. Filtering, parsing, pointer
18 management, time stamping and other functions can similarly be carried out using
19 hardware, software running on a suitably programmed processor or any
20 combination thereof.

21 While the present invention is described in terms of an exemplary digital Set-
22 Top Box for storage of A/V content. However, those skilled in the art will appreciate
23 that current broadband content delivery systems such as cable and satellite
24 television systems are also capable of delivery of other forms of content such as
25 Internet services, video, text, data, voice, fax, web pages and other information and
26 it is explicitly contemplated that the present invention can be used to store and
27 retrieve such data.

28 Those skilled in the art will recognize that the present invention has been
29 described in terms of exemplary embodiments based upon use of a programmed
30 processor. However, the invention should not be so limited, since the present

1 invention could be implemented using hardware component equivalents such as
2 special purpose hardware and/or dedicated processors which are equivalents to
3 the invention as described and claimed. Similarly, general purpose computers,
4 microprocessor based computers, micro-controllers, optical computers, analog
5 computers, dedicated processors and/or dedicated hard wired logic may be used
6 to construct alternative equivalent embodiments of the present invention.

7 Those skilled in the art will appreciate that the program steps and associated
8 data used to implement the embodiments described above can be implemented
9 other forms of storage including Read Only Memory (ROM) devices. The program
10 content storage, while preferably in solid state non-volatile memory such as flash
11 memory can also be carried out using volatile memory such as Random Access
12 Memory (RAM) devices and/or other equivalent storage technologies without
13 departing from the present invention. Such alternative storage devices should be
14 considered equivalents. Moreover, while some of the methods described in
15 conjunction with the present invention may be most advantageously carried out
16 using solid state non-volatile memory, they may also be applied to systems using
17 hard disc drive technology or other forms of electronic storage media without
18 departing from the invention.

19 The present invention is preferably implemented using a programmed
20 processor to control the processes described by executing programming
21 instructions that are broadly described above in flow chart form that can be stored
22 on any suitable electronic storage medium or transmitted over any suitable
23 electronic communication medium. However, those skilled in the art will
24 appreciate that the processes described above can be implemented in any number
25 of variations and in many suitable programming languages without departing from
26 the present invention. For example, the order of certain operations carried out can
27 often be varied, and additional operations can be added without departing from the
28 invention. Error trapping can be added and/or enhanced and variations can be
29 made in user interface and information presentation without departing from the
30 present invention. Such variations are contemplated and considered equivalent.